

Featuring GIO Cardoso, Grey 24x48 Rectified

cardoso

GIO
ARCHITECTURAL TILE + STONE

cardoso


Italian stone's sophisticated style interpreted in generous porcelain tile sizes and three dapper, authentically detailed colors–earthen elegance epitomized for modern design

INK JET COLORED BODY RECTIFIED FLOOR & WALL GLAZED PORCELAIN STONEWARE

GREY




GICRD2448GR
24" x 48" Rectified Field Tile




GICRD2424GR
24" x 24" Rectified Field Tile



GICRD1224GR
12" x 24" Rectified Field Tile



GICRD324BNGR
3" x 24" Bullnose



GICRDMOSGR
2" x 2" Mosaic



GICRD612CBGR
6" x 12" Cove Base

BIANCO



GICRD2448BI
24" x 48" Rectified Field Tile




GICRD2424BI
24" x 24" Rectified Field Tile



GICRD1224BI
12" x 24" Rectified Field Tile



GICRD324BNBI
3" x 24" Bullnose



GICRDMOSBI
2" x 2" Mosaic




GICRD612CBBI
6" x 12" Cove Base

ANTHRACITE



GICRD2448AN
24" x 48" Rectified Field Tile



GICRD2424AN
24" x 24" Rectified Field Tile



GICRD1224AN
12" x 24" Rectified Field Tile



GICRD324BNAN
3" x 24" Bullnose




GICRDMOSAN
2" x 2" Mosaic



GICRD612CBAN
6" x 12" Cove Base

SHADE VARIATION AND APPLICATIONS

V3



HEAVY VARIATION

	RESIDENTIAL	COMMERCIAL	INDUSTRIAL
Floor	•	•	•
Wall	•	•	•
Countertop	•	•	•

TECHNICAL SPECIFICATIONS

Description	Result	Test Method (Standard)
Chemical Resistance	RESISTANT	C650 Test
Water Absorption	0.5%	ISO 10545-3
PEI	4	C1027 Test
C.O.F. (Dynamic)	0.42	ANSI 137.1
Frost Resistance	RESISTANT	ASTM C1026
Thickness	8 mm	Factory Provided

PACKAGING

NOMINAL SIZE	PIECES PER BOX	SQ. FT. PER BOX	LBS. PER BOX	BOXES PER PALLET	SQ. FT. PER PALLET	WEIGHT PER PALLET
24x48 Rectified Field Tile	4	31.67	112.42	18	570	2220
12x24 Rectified Field Tile	8	15.75	56	32	504.03	1831
24x24 Rectified Field Tile	4	15.83	78	30	475	2318
3x24 Bullnose	16	-	32	-	-	-
2x2 Mosaic	5	4.90	17.80	-	-	-
6x12 Cove Base	8	-	15	-	-	-

G2 GREEN SQUARED
Certified by UL Environment