

Featuring GIO Atelier, Grey 8x40

atelier

GIO
ARCHITECTURAL TILE + STONE

atelier

Wood-look porcelain goes minimal for maximum style—the result is flawless Norwegian chic in four fresh, lightly grained hues in standard or chevron planks

INKJET RECTIFIED FLOOR & WALL GLAZED PORCELAIN STONEWARE

GREY





GIATL840GR
8" x 40" Rectified Field Tile



GIATL840CHGR
8" x 40" Rectified Chevron Field Tile



GIATL220BNGR
2" x 20" Bullnose

BIANCO



GIATL840BI
8" x 40" Rectified Field Tile

GIALT840CHBI
8" x 40" Rectified Chevron Field Tile

GIATL220BNBI
2" x 20" Bullnose

BEIGE





GIATL840BG
8" x 40" Rectified Field Tile



GIATL840CHBG
8" x 40" Rectified Chevron Field Tile



GIATL220BNBG
2" x 20" Bullnose

TAUPE





GIATL840TP
8" x 40" Rectified Field Tile



GIATL840CHTP
8" x 40" Rectified Chevron Field Tile



GIATL220BNTP
2" x 20" Bullnose

PACKAGING

NOMINAL SIZE	PIECES PER BOX	SQ. FT. PER BOX	LBS. PER BOX	BOXES PER PALLET	SQ. FT. PER PALLET	WEIGHT PER PALLET
8" x 40" Rectified Field Tile	6	12.92	56.88	36	465	2047.63
8" x 40" Rectified Chevron Field Tile	6	10.33	43.39	30	310	1301.60
2" x 20" Bullnose	10	-	17.60	-	-	-

SHADE VARIATION AND APPLICATIONS

V2



MODERATE VARIATION

	RESIDENTIAL	COMMERCIAL	INDUSTRIAL
Floor	•	•	•
Wall	•	•	•
Countertop	•	•	•

TECHNICAL SPECIFICATIONS

DESCRIPTION	RESULT	TEST METHOD (STANDARD)
PEI Rating	4	ASTM C-1027
Water Absorption	0.5%	ASTM C-323
C.O.F. (Dynamic)	0.42	ANSI 137.1
Chemical Resistance	EXCELLENT	ASTM C650
Thickness	9 mm	Factory Provided