

Featuring GIO Bergen, Natural 24" x 48" Rectified & Fluted Linear Wall Decor

bergen

GIO
ARCHITECTURAL TILE + STONE

bergen

creative, calm & clean natural warm wood aesthetics in 3 premium pattern porcelain options, paired with four modern colorations for full freedom in design functionality

INKJET RECTIFIED FLOOR & WALL GLAZED PORCELAIN STONEWARE, AVAILABLE IN HONED

ALMOND



GIBRG1060AL
10" x 60" Rectified Field Tile



GIBRG2448ALLND
24" x 48" Rectified & Fluted Linear Wall Decor



GIBRG2424ALLFD
24" x 24" Decoria

HONEY



GIBRG1060HO
10" x 60" Rectified Field Tile



GIBRG2448HOLND
24" x 48" Rectified & Fluted Linear Wall Decor



GIBRG2424HOLFD
24" x 24" Decoria

NATURAL



GIBRG1060NA
10" x 60" Rectified Field Tile



GIBRG2448NALND
24" x 48" Rectified & Fluted Linear Wall Decor



GIBRG2424NALFD
24" x 24" Decoria

NUT




GIBRG1060NU
10" x 60" Rectified Field Tile




GIBRG2424NULFD
24" x 24" Decoria

pattern options



SWIRL




FAN

PACKAGING

NOMINAL SIZE	PIECES PER BOX	SQ. FT. PER BOX	LBS. PER BOX	BOXES PER PALLET	SQ. FT. PER PALLET	WEIGHT PER PALLET
10x60 Rectified Field Tile	3	12.11	51.99	30	363.30	1559.70
24x24 Rectified & Fluted Linear Wall Decor	3	11.62	47.10	40	464.80	1884
24x48 Decoria	2	15.50	65.04	35	542.50	2276.40

SHADE VARIATION AND APPLICATIONS

V2



MODERATE VARIATION

	RESIDENTIAL	COMMERCIAL	INDUSTRIAL
Floor	•	•	•
Wall	•	•	•
Countertop	•	•	•

TECHNICAL SPECIFICATIONS

Description	Result	Test Method (Standard)
Chemical Resistance	RESISTANT	C650 Test
Water Absorption	0.05%	ISO 10545-3
PEI	4	C1027 Test
C.O.F. (Dynamic)	0.42 (Floor Options Only)	ANSI 137.1
Frost Resistance	RESISTANT	ASTM C1026
Thickness	9 mm	Factory Provided