

Featuring GIO Bianca, Carrara 24 x 48 Polished & Rectified

GIO
ARCHITECTURAL TILE + STONE

bianca

Classically contemporary, timelessly on-trend–this marble-look captures carrara's striations and variations in large and mosaic sizes in polished or matte finishes

INKJET RECTIFIED FLOOR & WALL GLAZED PORCELAIN STONEWARE
AVAILABLE IN BOTH POLISHED & MATTE FINISHES

CARRARA



GIBIA2448CAM
24" x 48" Matte & Rectified Field Tile
GIBIA2448CAP
24" x 48" Polished & Rectified Field Tile



GIBIA2424CAM
24" x 24" Matte Field Tile
GIBIA2424CAP
24" x 24" Polished & Rectified Field Tile




GIBIA1224CAM
12" x 24" Matte Field Tile
GIBIA1224CAP
12" x 24" Polished & Rectified Field Tile



GIBIA312BNCAM
3" x 12" Matte Bullnose
GIBIA312BNCAP
3" x 12" Polished Bullnose



GIBIA33HXCAM
3" x 3" Matte Hexagon Mosaic
GIBIA33HXCAP
3" x 3" Polished Hexagon Mosaic



GIBIAMOSCAM
2" x 2" Matte Mosaic
GIBIAMOSCAP
2" x 2" Polished Mosaic

NUVOLATO SILK



GIBIA2448NSM
24" x 48" Matte & Rectified Field Tile
GIBIA2448NSP
24" x 48" Polished & Rectified Field Tile



GIBIA2424NSM
24" x 24" Matte Field Tile
GIBIA2424NSP
24" x 24" Polished & Rectified Field Tile

GIBIA1224NSM
12" x 24" Matte Field Tile
GIBIA1224NSP
12" x 24" Polished & Rectified Field Tile

GIBIA312BNNSM
3" x 12" Matte Bullnose
GIBIA312BNNSP
3" x 12" Polished Bullnose

GIBIA33HXNSM
3" x 3" Matte Hexagon Mosaic
GIBIA33HXNSP
3" x 3" Polished Hexagon Mosaic



GIBIAMOSNSM
2" x 2" Matte Mosaic
GIBIAMOSNSP
2" x 2" Polished Mosaic

PACKAGING


NOMINAL SIZE	PIECES PER BOX	SQ. FT. PER BOX	LBS. PER BOX	BOXES PER PALLET	SQ. FT. PER PALLET	WEIGHT PER PALLET
24x48 Field Tile	2	16	76.80	32	512	2457.60
24x24 Field Tile	4	16	52.80	36	576	1900
12x24 Field Tile	8	16	52.80	48	786	2534
2x2 Mosaic	10	-	33	45	-	1485
3x12 Bullnose	15	-	14.66	168	-	2444.40
3x3 Hexagon Mosaic	10	-	33	45	-	1485

TECHNICAL SPECIFICATIONS

Description	Result	Test Method (Standard)
Chemical Resistance	RESISTANT	C650 Test
Water Absorption	0.5%	ISO 10545-3
PEI	4	C1027 Test
C.O.F. (Dynamic)	0.42 (Polished NOT COMPLIANT)	ANSI 137.1
Frost Resistance	RESISTANT	ASTM C1026
Thickness	8 mm (24x48 - 10 mm)	Factory Provided

SHADE VARIATION AND APPLICATIONS

V3



HEAVY VARIATION

	RESIDENTIAL	COMMERCIAL	INDUSTRIAL
Floor	•	•	•
Wall	•	•	•
Countertop	•	•	•