

Featuring GIO Corton, Beige 36x36 Honed & Rectified Field Tile

corton

a fashionable french limestone inspired porcelain pallet
complete with sophisticated sizes and high fashion finishes

INKJET RECTIFIED FLOOR, WALL & PAVER GLAZED PORCELAIN STONEWARE

WHITE



GICOR3636WT
36″ x 36″ Honed & Rectified Field Tile



GICOR2448WT
24″ x 48″ Honed & Rectified Field Tile
GICOR2448WTF
24″ x 48″ Flamed & Rectified Field Tile



GICOR2424WTPVR[i/o]
24″ x 24″ Honed & Rectified Paver



GICOR1224WT
12″ x 24″
Honed & Rectified
Field Tile



GICORMOSWT
12″ x 12″ Honed
Basketweave Mosaic



GICOR424BNWT
4″ x 24″ Honed Bullnose

GRAY




GICOR3636GR
36″ x 36″ Honed & Rectified Field Tile



GICOR2448GR
24″ x 48″ Honed & Rectified Field Tile
GICOR2448GRF
24″ x 48″ Flamed & Rectified Field Tile



GICOR2424GRPVR[i/o]
24″ x 24″ Honed & Rectified Paver



GICOR1224GR
12″ x 24″
Honed & Rectified
Field Tile



GICORMOSGR
12″ x 12″ Honed
Basketweave Mosaic



GICOR424BNGR
4″ x 24″ Honed Bullnose

BEIGE



GICOR3636BE
36″ x 36″ Honed & Rectified Field Tile



GICOR2448BE
24″ x 48″ Honed & Rectified Field Tile
GICOR2448BEF
24″ x 48″ Flamed & Rectified Field Tile



GICOR2424BEPVR[i/o]
24″ x 24″ Honed & Rectified Paver



GICOR1224BE
12″ x 24″
Honed & Rectified
Field Tile



GICORMOSBE
12″ x 12″ Honed
Basketweave Mosaic



GICOR424BNBE
4″ x 24″ Honed Bullnose

TAUPE



GICOR3636TP
36″ x 36″ Honed & Rectified Field Tile



GICOR2448TP
24″ x 48″ Honed & Rectified Field Tile
GICOR2448TPF
24″ x 48″ Flamed & Rectified Field Tile



GICOR1224TP
12″ x 24″
Honed & Rectified
Field Tile



GICORMOSTP
12″ x 12″ Honed
Basketweave Mosaic



GICOR424BNTP
4″ x 24″ Honed Bullnose

PACKAGING

NOMINAL SIZE	PIECES PER BOX	SQ. FT. PER BOX	LBS. PER BOX	BOXES PER PALLET	SQ. FT. PER PALLET	WEIGHT PER PALLET
36x36 Rectified Field Tile	2	17.40	78.20	30	522	2346
24x48 Rectified Field Tile	2	15.39	64.98	40	615.70	2649
12x24 Rectified Field Tile	8	15.62	58.20	32	499.84	1912
24x24 Rectified Paver	2	7.79	69	36	280.44	2534
Basketweave Mosaic	5	4.84	19.40	90	435.60	1796
4x24 Bullnose	16	-	39.46	-	-	-


i/o - INSIDE AND OUTSIDE

TECHNICAL SPECIFICATIONS

Description	Result	Test Method (Standard)
Chemical Resistance	RESISTANT	C650 Test
Water Absorption	0.5%	ISO 10545-3
PEI	4	C1027 Test
C.O.F. (Dynamic)	0.42 (0.64 - Paver)	ANSI 137.1
Frost Resistance	RESISTANT	ASTM C1026
Thickness	9 mm (20mm Paver)	Factory Provided

SHADE VARIATION AND APPLICATIONS

V2



MODERATE VARIATION

	RESIDENTIAL	COMMERCIAL	INDUSTRIAL
Floor	•	•	•
Wall	•	•	•
Countertop	•	•	•