

Featuring GIO Crema_Avorio, 24 x 48 Polished & Rectified

crema_avorio

An expression of prestigious Sicilian marble and rich veining interpreted in a plush porcelain palette

INKJET RECTIFIED POLISHED AND HONED, FLOOR & WALL GLAZED PORCELAIN STONEWARE





GICRA2424H
24″x 24″
Antique Honed & Rectified Field Tile



GICRA2448P
24″x 48″
Polished & Rectified Field Tile



GICRA1224P
12″x 24″
Polished & Rectified Field Tile

GICRA1224H
12″x 24″
Antique Honed & Rectified Field Tile



GICRA624H
6″x 24″
Antique Honed & Rectified Field Tile



GICRA424H
4″x 24″
Antique Honed & Rectified Field Tile



GICRASMOS
1″x 3″
AntiqueHoned Stacked Mosaic

PACKAGING

NOMINAL SIZE	PIECES PER BOX	SQ. FT. PER BOX	LBS. PER BOX	BOXES PER PALLET	SQ. FT. PER PALLET	WEIGHT PER PALLET
24x48 Rectified Field Tile	2	15.50	72.74	30	465	2182.20
24x24 Rectified Field Tile	3	11.62	54.24	40	464.80	2169.60
12x24 Rectified Field Tile	3	11.62	54.24	40	464.80	2169.60
6x24 Rectified Field Tile	14	13.56	66	-	-	-
4x24 Rectified Field Tile	18	11.61	60	-	-	-
1x3 Stacked Mosaic	10	10	50	-	-	-

100 sq. ft. minimum

SHADE VARIATION AND APPLICATIONS

V3



HEAVY VARIATION

	RESIDENTIAL	COMMERCIAL	INDUSTRIAL
Floor	•	•	•
Wall	•	•	•
Countertop	•	•	•

TECHNICAL SPECIFICATIONS

Description	Result	Test Method (Standard)
Chemical Resistance	RESISTANT	C650 Test
Water Absorption	0.5%	ISO 10545-3
PEI	4	C1027 Test
C.O.F. (Dynamic)	Honed - 0.42	ANSI 137.1
C.O.F. (Dynamic)	Polished - Not Compliant	ANSI 137.1
Frost Resistance	RESISTANT	ASTM C1026
Thickness	10 mm	Factory Provided