

Featuring GIO Jura, Light Beige 24x48 Rectified Field Tile

jura

GIO
ARCHITECTURAL TILE + STONE

jura

rich, neutral and light organic tones, blended with fossils and shells in a timeless limestone interpretation, available in a trio of finishes

COLORBODY INKJET FLOOR, WALL & PAVER GLAZED PORCELAIN STONEWARE

LIGHT BEIGE



GIJUR2448LB
24" x 48" Honed & Rectified Field Tile



GIJUR1224LB
12" x 24"
Honed & Rectified Field Tile



GIJUR22MOSLB
2" x 2" Mosaic



GIJUR312BNLB
3" x 12" Bullnose



GIJUR2448LBL
24" x 48" Linear Rectified Field Tile



GIJUR1224LBL
12" x 24"
Linear Field Tile



GIPAV2448JRLB i/o
24" x 48" Porcelain Paver




GIPAV2424JRLB i/o
24" x 24" Porcelain Paver

PACKAGING

NOMINAL SIZE	PIECES PER BOX	SQ. FT. PER BOX	LBS. PER BOX	BOXES PER PALLET	SQ. FT. PER PALLET	WEIGHT PER PALLET
24x48 Rectified Field Tile	2	16	55	36	576	2034
12x24 Rectified Field Tile	6	12	41	48	576	1968
24x48 Linear Rectified Field Tile	2	16	55	36	576	2034
12x24 Linear Rectified Field Tile	6	12	41	48	576	1968
24x48 Porcelain Paver	2	16	144	16	256	2304
24x24 Porcelain Paver	2	8	72	36	288	2592
2x2 Mosaic	10	-	40	-	-	-
3x12 Bullnose	12	-	12.90	-	-	-

SHADE VARIATION AND APPLICATIONS

V2



MODERATE VARIATION

	RESIDENTIAL	COMMERCIAL	INDUSTRIAL
Floor	•	•	•
Wall	•	•	•
Countertop	•	•	•

TECHNICAL SPECIFICATIONS

Description	Result	Test Method (Standard)
Chemical Resistance	RESISTANT	C650 Test
Water Absorption	0.5%	ISO 10545-3
PEI	4	C1027 Test
C.O.F. (Dynamic)	0.5 (Paver - 0.75)	ANSI 137.1
Frost Resistance	RESISTANT	ASTM C1026
Thickness	8 mm (Paver - 20 mm)	Factory Provided

i/o - INSIDE AND OUTSIDE