

Featuring GIO Maximus, Grey 24x48 Rectified

maximus


GIO
ARCHITECTURAL TILE + STONE

maximus

A travertine look of a different stripe with natural, linear detailing and dramatic, true stone colors for maximum impact

INKJET COLORED BODY RECTIFIED FLOOR & WALL GLAZED PORCELAIN STONEWARE

TAUPE



GIMX1224TP
12″ x 24″
Rectified Field Tile



GIMX2448TP
24″ x 48″
Rectified Field Tile



GIMX424BNTP
4″ x 24″
Bullnose



GIMXMOSTP
2″ x 2″
Mosaic

BIANCO



GIMX1224BI
12″ x 24″
Rectified Field Tile



GIMX2448BI
24″ x 48″
Rectified Field Tile



GIMX424BNBI
4″ x 24″
Bullnose



GIMXMOSBI
2″ x 2″
Mosaic

GREY



GIMX1224GR
12″ x 24″
Rectified Field Tile



GIMX2448GR
24″ x 48″
Rectified Field Tile



GIMX424BNGR
4″ x 24″
Bullnose



GIMXMOSGR
2″ x 2″
Mosaic

PACKAGING

NOMINAL SIZE	PIECES PER BOX	SQ. FT. PER BOX	LBS. PER BOX	BOXES PER PALLET	SQ. FT. PER PALLET	WEIGHT PER PALLET
24″ x 48″ Rectified Field Tile	4	31.67	112.42	18	570	2220
12″ x 24″ Rectified Field Tile	8	15.75	56	32	504.03	1831
2″ x 2″ Mosaic	5	–	17.80	–	–	–
4″ x 24″ Bullnose	16	–	47.27	–	–	–

TECHNICAL SPECIFICATIONS

DESCRIPTION	RESULT	TEST METHOD (STANDARD)
Water Absorption	0.05%	C373 Test
C.O.F. (Dynamic)	0.42	ANSI 137.1
Frost Resistance	RESISTANT	ASTM C1026
Breaking Strength	350 lbs.	ASTMC648
PEI Rating	4	ASTM C-1027
Thickness	8 mm	Factory Provided

SHADE VARIATION AND APPLICATIONS

V2



MODERTE VARIATION

	RESIDENTIAL	COMMERCIAL	INDUSTRIAL
Floor	•	•	•
Wall	•	•	•
Countertop	•	•	•

G2 GREEN SQUARED
Certified by UL Environment