

Featuring GIO Mural, Aqua Onyx 24x48 Polished & Rectified

mural


mural

Bring the bold art of nature to your wall-to-wall interior design with this daring collection of polished, 24x48 tiles in two stunning groupings–sumptuous marbles and two animal-inspired styles

INKJET POLISHED & RECTIFIED FLOOR & WALL GLAZED PORCELAIN STONEWARE - GROUP 1
GROUP 2 - WALL ONLY


group 1

AQUA ONYX




GIMUR2448AQ
24" x 48" Polished & Rectified Field Tile

AZUL




GIMUR2448AZ
24" x 48" Polished & Rectified Field Tile

DARK



GIMUR2448DK
24" x 48" Polished & Rectified Field Tile

VERDE



GIMUR2448IG
24" x 48" Polished & Rectified Field Tile

DOLOMITE VEIN




GIMUR2448DV
24" x 48" Polished & Rectified Field Tile

GRIGIO



GIMUR2448GR
24" x 48" Polished & Rectified Field Tile

MARQUINA GRAND



GIMUR2448MG
24" x 48" Polished & Rectified Field Tile

GREY CANNELA



GIMUR2448RO
24" x 48" Polished & Rectified Field Tile

RAINFOREST



GIMUR2448RF
24" x 48" Polished & Rectified Field Tile

VEINA



GIMUR2448VE
24" x 48" Polished & Rectified Field Tile

CREMA



GIMUR2448CR
24" x 48" Polished & Rectified Field Tile

group 2 (wall only)

LEOPARD




GIMUR2448LE
24" x 48" Polished & Rectified Field Tile

SNAKE




GIMUR2448SN
24" x 48" Polished & Rectified Field Tile

CROC



GIMUR2448CR
24" x 48" Polished & Rectified Field Tile

PYTHON



GIMUR2448PY
24" x 48" Polished & Rectified Field Tile

PACKAGING

NOMINAL SIZE	PIECES PER BOX	SQ. FT. PER BOX	LBS. PER BOX	BOXES PER PALLET	SQ. FT. PER PALLET	WEIGHT PER PALLET
24" x 48" Polished & Rectified Field Tile (Group 1)	4	31	106	16	496	1696
24" x 48" Polished & Rectified Field Tile (Dark, Grigio & Azul - Group 1)	3	23.25	83	30	697.50	2490
24" x 48" Polished & Rectified Field Tile (Group 2)	2	15.5	54	24	372	1272

TECHNICAL SPECIFICATIONS

Description	Result	Test Method (Standard)
Chemical Resistance	RESISTANT	C650 Test
Water Absorption	0.5%	ISO 10545-3
PEI	4	C1027 Test
C.O.F. (Dynamic)	Not Compliant (wall only)	ANSI 137.1
Frost Resistance	RESISTANT	ASTM C1026
Thickness	6.5 mm	Factory Provided

SHADE VARIATION AND APPLICATIONS

V3



HEAVY VARIATION

	RESIDENTIAL	COMMERCIAL	INDUSTRIAL
Floor	•		
Wall	•	•	•
Countertop			