

Featuring GIO Quarzo 24" x 48" Polished & Rectified Field Tile

quarzo

GIO
ARCHITECTURAL TILE + STONE

quarzo

modern marble aesthetics married with soft, smooth & subtle veined variation, blended with warm ivory tonality

INKJET RECTIFIED POLISHED AND MATTE FLOOR & WALL GLAZED PORCELAIN STONEWARE



GISLB48110BQZPO
48" x 110" Polished & Rectified Panel



GISLB2448BQZ
24" x 48" Matte Rectified Field Tile

GISLB2448BQZPO
24" x 48" Polished & Rectified Field Tile



GISLBMOSBQZ
2" x 2" Matte Mosaic




GISLBBWMOSBQZ
Polished Basketweave Mosaic



GISLB324BNBQZ
3" x 24" Matte Rectified Bullnose

GISLB324BNBQZPO
3" x 24" Polished & Rectified Bullnose



GISLB1224BQZ
12" x 24" Matte Rectified Field Tile

GISLB1224BQZPO
12" x 24" Polished & Rectified Field Tile

GISLB312BQZ
3" x 12" Matte Rectified Field Tile

PACKAGING


NOMINAL SIZE	PIECES PER BOX	SQ. FT. PER BOX	LBS. PER BOX	BOXES PER PALLET	SQ. FT. PER PALLET	WEIGHT PER PALLET
48x110 Rectified Panel (A-Frame needed for shipment)	1	35.91	117	1	35.91	117
24x48 Rectified Field Tile	2	15.50	76	36	558	2520
12x24 Rectified Field Tile	6	11.63	55	48	558.24	2520
3x12 Rectified Field Tile	36	8.72	41	56	488.32	2268
2x2 Mosaic	5	-	23	-	-	-
Basketweave Mosaic	5	-	23	-	-	-
3x24 Bullnose	15	-	32	-	-	-

TECHNICAL SPECIFICATIONS

Description	Result	Test Method (Standard)
Chemical Resistance	RESISTANT	C650 Test
Water Absorption	0.05%	ISO 10545-3
PEI	5	C1027 Test
C.O.F. (Dynamic)	Matte - 0.42	ANSI 137.1
C.O.F. (Dynamic)	Polished - NOT COMPLIANT	ANSI 137.1
Frost Resistance	RESISTANT	ASTM C1026
Thickness	9.5 mm (48x110 - 6.5 mm)	Factory Provided

SHADE VARIATION AND APPLICATIONS

V3



HEAVY VARIATION

	RESIDENTIAL	COMMERCIAL	INDUSTRIAL
Floor	•	•	•
Wall	•	•	•
Countertop	•	•	•