

Featuring GIO Simplestone, Gray 12x24 Matte & Rectified Field Tile

simplestone

simplestone

minimalist modern style in a versatile variety of sizes and shapes in high performance porcelain with pavers suitable for settings indoor and out!

INKJET RECTIFIED FLOOR, WALL & PAVER GLAZED PORCELAIN STONEWARE

WHITE

GISIM2448WT
24" x 48" Matte & Rectified
Field Tile

GISIM2424WT
24" x 24" Matte & Rectified
Field Tile

GIPAV2424SGY i/o
24" x 24" Matte & Rectified
Field Tile/Porcelain Paver

GISIM1224WT
12" x 24" Matte & Rectified
Field Tile

GISIMMOSWT
1" x 1" Mosaic

GISIM424BNWT
4" x 24" Bullnose

BEIGE



GISIM2448BE
24" x 48" Matte & Rectified
Field Tile



GISIM2424BE
24" x 24" Matte & Rectified
Field Tile



GIPAV2424SBE i/o
24" x 24" Matte & Rectified
Field Tile/Porcelain Paver



GISIM1224BE
12" x 24" Matte & Rectified
Field Tile



GISIMMOSBE
1" x 1" Mosaic



GISIM424BNBE
4" x 24" Bullnose

GRAY



GISIM2448GR
24" x 48" Matte & Rectified
Field Tile



GISIM2424GR
24" x 24" Matte & Rectified
Field Tile



GIPAV2424SGY i/o
24" x 24" Matte & Rectified
Field Tile/Porcelain Paver



GISIM1224GR
12" x 24" Matte & Rectified
Field Tile



GISIMMOSGR
1" x 1" Mosaic




GISIM424BNGR
4" x 24" Bullnose

GRAPHITE



GISIM2448GPT
24" x 48" Matte & Rectified
Field Tile




GISIM2424GPT
24" x 24" Matte & Rectified
Field Tile



GIPAV2424SGR i/o
24" x 24" Matte & Rectified
Field Tile/Porcelain Paver



GISIM1224GPT
12" x 24" Matte & Rectified
Field Tile



GISIMMOSGPT
1" x 1" Mosaic



GISIM424BNGPT
4" x 24" Bullnose

PACKAGING

NOMINAL SIZE	PIECES PER BOX	SQ. FT. PER BOX	LBS. PER BOX	BOXES PER PALLET	SQ. FT. PER PALLET	WEIGHT PER PALLET
24x24 Rectified Field Tile	6	23.25	91	24	558	2236
24x48 Rectified Field Tile	2	15.50	61	36	558	2236
12x24 Rectified Field Tile	8	15.60	61.40	32	496	1934
24x24 Rectified Paver	2	7.75	71.17	32	248	2277.30
1x1 Mosaic	10	9.70	36	-	-	-
4x24 Bullnose	10	-	22	-	-	-


i/o - INSIDE AND OUTSIDE

TECHNICAL SPECIFICATIONS

Description	Result	Test Method (Standard)
Chemical Resistance	RESISTANT	C650 Test
Water Absorption	0.1%	ISO 10545-3
PEI	4	C1027 Test
C.O.F. (Dynamic)	0.42 (0.60 - Paver)	ANSI 137.1
Frost Resistance	RESISTANT	ASTM C1026
Thickness	8.5mm (20mm Paver)	Factory Provided

SHADE VARIATION AND APPLICATIONS

V2



MODERATE VARIATION

	RESIDENTIAL	COMMERCIAL	INDUSTRIAL
Floor	•	•	•
Wall	•	•	•
Countertop	•	•	•