Featuring GIO Slate_Montauk, Charcoal 24x24 Rectified Field Tile

slate_montauk

depth and dark tones meet classic cleft in this porcelain perfect slate interpretation,
lush large format or linear sizes available for various applications & aesthetic appeal

INKJET RECTIFIED FLOOR & WALL GLAZED PORCELAIN STONEWARE


LIGHT GREY



GIOSLM2448LG
24" x 48" Rectified Field Tile



GIOSLM2424LG
24" x 24" Rectified Field Tile



GIOSLM848LG
8" x 48" Rectified
Field Tile



GIOSLM624LG
4" x 24" Rectified
Field Tile



GIOSLM1224LG
12" x 24" Rectified
Field Tile

IVORY



GIOSLM2448IV
24" x 48" Rectified Field Tile




GIOSLM2424IV
24" x 24" Rectified Field Tile



GIOSLM848IV
8" x 48" Rectified
Field Tile



GIOSLM624IV
4" x 24" Rectified
Field Tile




GIOSLM1224IV
12" x 24" Rectified
Field Tile


CHARCOAL



GIOSLM2448CH
24" x 48" Rectified Field Tile




GIOSLM2424CH
24" x 24" Rectified Field Tile



GIOSLM848CH
8" x 48" Rectified
Field Tile



GIOSLM624CH
4" x 24" Rectified
Field Tile



GIOSLM1224CH
12" x 24" Rectified
Field Tile

PACKAGING


NOMINAL SIZE	PIECES PER BOX	SQ. FT. PER BOX	LBS. PER BOX	BOXES PER PALLET	SQ. FT. PER PALLET	WEIGHT PER PALLET
24x24 Rectified Field Tile	4	15.50	70	32	496	2240
24x48 Rectified Field Tile	2	15.50	70.10	36	558	2523.60
12x24 Special Cut Rectified Field Tile	-	-	-	-	-	-
8x48 Special Cut Rectified Field Tile	-	-	-	-	-	-
4x24 Special Cut Rectified Field Tile	-	-	-	-	-	-

TECHNICAL SPECIFICATIONS

Description	Result	Test Method (Standard)
Chemical Resistance	RESISTANT	C650 Test
Water Absorption	0.5%	ISO 10545-3
PEI	4	C1027 Test
C.O.F. (Dynamic)	0.42	ANSI 137.1
Frost Resistance	RESISTANT	ASTM C1026
Thickness	9 mm	Factory Provided

SHADE VARIATION AND APPLICATIONS

V3



HEAVY VARIATION

	RESIDENTIAL	COMMERCIAL	INDUSTRIAL
Floor	•	•	•
Wall	•	•	•
Countertop	•	•	•

100 sq. ft. minimum