

Featuring GIO Taj, 24" x 48" Matte Rectified Field Tile

GIO
ARCHITECTURAL TILE + STONE

taj

sophisticated shades & subtle veining of warm ivory and gold quartzite in a timeless take in marble aesthetics, packaged in polished or matte porcelain for durable decadent design

INKJET RECTIFIED POLISHED AND MATTE FLOOR & WALL GLAZED PORCELAIN STONEWARE



GITAJ2448
24" x 48" Matte Rectified Field Tile
GITAJ2448PO
24" x 48" Polished & Rectified Field Tile




GITAJ1224
12" x 24" Matte Rectified Field Tile
GITAJ1224PO
12" x 24" Polished & Rectified Field Tile



GITAJ3636
36" x 36" Matte Rectified Field Tile
GITAJ3636PO
36" x 36" Polished & Rectified Field Tile



GITAJMOS
2" x 2" Rectified Mosaic




GITAJ424BN
4" x 24" Matte Bullnose
GITAJ424BNPO
4" x 24" Polished Bullnose

PACKAGING

NOMINAL SIZE	PIECES PER BOX	SQ. FT. PER BOX	LBS. PER BOX	BOXES PER PALLET	SQ. FT. PER PALLET	WEIGHT PER PALLET
24x48 Rectified Field Tile	2	15.39	64.98	40	615.70	2649
36x36 Rectified Field Tile	2	17.40	78.20	30	522	2346
12x24 Rectified Field Tile	8	15.62	58.20	32	499.84	1912
2x2 Mosaic	5	4.84	17.64	-	-	-
4x24 Bullnose	16	-	39.46	-	-	-

SHADE VARIATION AND APPLICATIONS

V3



HEAVY VARIATION

	RESIDENTIAL	COMMERCIAL	INDUSTRIAL
Floor	•	•	•
Wall	•	•	•
Countertop	•	•	•

TECHNICAL SPECIFICATIONS

Description	Result	Test Method (Standard)
Chemical Resistance	RESISTANT	C650 Test
Water Absorption	0.05%	ISO 10545-3
PEI	4	C1027 Test
C.O.F. (Dynamic)	0.42 (Matte)	ANSI 137.1
C.O.F. (Dynamic)	Not Compliant (polished)	ANSI 137.1
Frost Resistance	RESISTANT	ASTM C1026
Thickness	9 mm	Factory Provided