

Featuring GIO Umber, Bianco 8x48 Rectified

umber

Wood's classic look in four fresh tones interpreted in powerful porcelain planks and exterior paver–always on trend, inside or out

INKJET COLOR BODY RECTIFIED FLOOR & WALL GLAZED PORCELAIN STONEWARE

BIANCO





GIUMB848BI
8" x 48" Rectified Field Tile



GIUMB1248BI i/o
12" x 48" Rectified Field Tile/Porcelain Paver



GIUMB336BNBI
3" x 36" Bullnose

GREY





GIUMB848GR
8" x 48" Rectified Field Tile



GIUMB1248GR i/o
12" x 48" Rectified Field Tile/Porcelain Paver



GIUMB336BNGR
3" x 36" Bullnose

AMBER





GIUMB848AM
8" x 48" Rectified Field Tile




GIUMB1248AM i/o
12" x 48" Rectified Field Tile/Porcelain Paver



GIUMB336BNAM
3" x 36" Bullnose

NOCE






GIUMB848NO
8" x 48" Rectified Field Tile



GIUMB336BNNO
3" x 36" Bullnose

SHADE VARIATION AND APPLICATIONS

V3



HEAVY VARIATION

	RESIDENTIAL	COMMERCIAL	INDUSTRIAL
Floor	•	•	•
Wall	•	•	•
Countertop	•	•	•

PACKAGING

NOMINAL SIZE	PIECES PER BOX	SQ. FT. PER BOX	LBS. PER BOX	BOXES PER PALLET	SQ. FT. PER PALLET	WEIGHT PER PALLET
8x48 Rectified Field Tile	6	16	75	24	384.48	1805
12x48 Rectified Paver	4	16	147	16	256	2355
3x36 Bullnose	16	-	33.60	-	-	-

TECHNICAL SPECIFICATIONS

Description	Result	Test Method (Standard)
Chemical Resistance	RESISTANT	C650 Test
Water Absorption	0.5%	ISO 10545-3
PEI	4	C1027 Test
C.O.F. (Dynamic)	0.63	ANSI 137.1
Frost Resistance	RESISTANT	ASTM C1026
Thickness	10 mm (20 mm Paver)	Factory Provided

i/o - INSIDE AND OUTSIDE