

Featuring GIO Veneziano, Crema Linen 24″ x 48″ Natural Structured Rectified Field Tile

veneziano

GIO
ARCHITECTURAL TILE + STONE

veneziano

experience dramatic design and durability assembled with historical hues of venice terrazzo packaged in porcelain stoneware of versatile sizes, shapes and structures

INKJET COLOR BODY PORCELAIN STONEWARE FLOOR & WALL TILES AVAILABLE IN SEMI-POLISHED & NATURAL STRUCTURED FINISHES

BLEACHED BROWN



GIVNZ2448BRP
24" x 48" Semi-Polished Rectified Field Tile

GIVNZ2448BRS
24" x 48" Natural Structured Rectified Field Tile



GIVNZ2424BRP
24" x 24" Semi-Polished Rectified Field Tile

GIVNZ2424BRS
24" x 24" Natural Structured Rectified Field Tile



GIVNZ1224BRP
12" x 24" Semi-Polished Rectified Field Tile

GIVNZ1224BRS
12" x 24" Natural Structured Rectified Field Tile



GIVNZ412BNBRP
4" x 24" Semi-Polished Bullnose

GIVNZ412BNBRS
4" x 24" Natural Structured Bullnose

DARK GREY




GIVNZ2448DGP
24" x 48" Semi-Polished Rectified Field Tile

GIVNZ2448DGS
24" x 48" Natural Structured Rectified Field Tile



GIVNZ2424DGP
24" x 24" Semi-Polished Rectified Field Tile

GIVNZ2424DGS
24" x 24" Natural Structured Rectified Field Tile



GIVNZ1224DGP
12" x 24" Semi-Polished Rectified Field Tile

GIVNZ1224DGS
12" x 24" Natural Structured Rectified Field Tile



GIVNZ412BNDGP
4" x 24" Semi-Polished Bullnose

GIVNZ412BNDGS
4" x 24" Natural Structured Bullnose

LIGHT GREY



GIVNZ2448LGP
24" x 48" Semi-Polished Rectified Field Tile

GIVNZ2448LGS
24" x 48" Natural Structured Rectified Field Tile




GIVNZ2424LGP
24" x 24" Semi-Polished Rectified Field Tile

GIVNZ2424LGS
24" x 24" Natural Structured Rectified Field Tile



GIVNZ1224LGP
12" x 24" Semi-Polished Rectified Field Tile

GIVNZ1224LGS
12" x 24" Natural Structured Rectified Field Tile



GIVNZ412BNLGP
4" x 24" Semi-Polished Bullnose

GIVNZ412BNLGS
4" x 24" Natural Structured Bullnose

CREMA LINEN



GIVNZ2448LNP
24" x 48" Semi-Polished Rectified Field Tile

GIVNZ2448LNS
24" x 48" Natural Structured Rectified Field Tile




GIVNZ2424LNP
24" x 24" Semi-Polished Rectified Field Tile

GIVNZ2424LNS
24" x 24" Natural Structured Rectified Field Tile



GIVNZ1224LNP
12" x 24" Semi-Polished Rectified Field Tile

GIVNZ1224LNS
12" x 24" Natural Structured Rectified Field Tile



GIVNZ412BNLNP
4" x 24" Semi-Polished Bullnose

GIVNZ412BNLNS
4" x 24" Natural Structured Bullnose

SAND BEIGE



GIVNZ2448SDP
24" x 48" Semi-Polished Rectified Field Tile

GIVNZ2448SDS
24" x 48" Natural Structured Rectified Field Tile



GIVNZ2424SDP
24" x 24" Semi-Polished Rectified Field Tile

GIVNZ2424SDS
24" x 24" Natural Structured Rectified Field Tile



GIVNZ1224SDP
12" x 24" Semi-Polished Rectified Field Tile

GIVNZ1224SDS
12" x 24" Natural Structured Rectified Field Tile



GIVNZ412BNSDP
4" x 24" Semi-Polished Bullnose

GIVNZ412BNSDS
4" x 24" Natural Structured Bullnose

STONE WHITE




GIVNZ2448WTP
24" x 48" Semi-Polished Rectified Field Tile

GIVNZ2448WTS
24" x 48" Natural Structured Rectified Field Tile



GIVNZ2424WTP
24" x 24" Semi-Polished Rectified Field Tile

GIVNZ2424WTS
24" x 24" Natural Structured Rectified Field Tile



GIVNZ1224WTP
12" x 24" Semi-Polished Rectified Field Tile

GIVNZ1224WTS
12" x 24" Natural Structured Rectified Field Tile



GIVNZ412BNWTP
4" x 24" Semi-Polished Bullnose


GIVNZ412BNWTS
4" x 24" Natural Structured Bullnose

PACKAGING

NOMINAL SIZE	PIECES PER BOX	SQ. FT. PER BOX	LBS. PER BOX	BOXES PER PALLET	SQ. FT. PER PALLET	WEIGHT PER PALLET
24x48 Field Tile	2	15.50	55.03	35	542.50	1926.05
24x24 Field Tile	4	15.50	55.03	32	496	1760.96
12x24 Field Tile	8	15.50	59.37	32	496	1899.84
4x24 Bullnose	16	10.33	32	-	-	-

SHADE VARIATION AND APPLICATIONS

V2



MODERATE VARIATION

	RESIDENTIAL	COMMERCIAL	INDUSTRIAL
Floor	•	•	•
Wall	•	•	•
Countertop	•	•	•

TECHNICAL SPECIFICATIONS

Description	Result	Test Method (Standard)
Chemical Resistance	RESISTANT	C650 Test
Water Absorption	0.50%	ISO 10545-3
PEI	4	C1027 Test
C.O.F. (Dynamic)	0.42 (Structured)	ANSI 137.1
C.O.F. (Dynamic)	Not Compliant (Semi-polished)	ANSI 137.1
Frost Resistance	RESISTANT	ASTM C1026
Thickness	8 mm	Factory Provided