

Featuring GIO Amani, Light Grey Polished 24x24

GIO
ARCHITECTURAL TILE + STONE

amani

A look in the vein of strongly striated natural stone—honed or polished multi-directional in a quartet of natural neutrals

INK JET RECTIFIED POLISHED & MATTE, FLOOR & WALL GLAZED PORCELAIN STONEWARE

BEIGE





GIAMA2424BGPO
24" x 24"
Polished and Rectified Field Tile



GIAMA1224BGPO
12" x 24" Polished and Rectified Field Tile


GIAMA1224BGMT
12" x 24" Matte Rectified Field Tile

GIAMA2448BGPO
24" x 48"
Polished and Rectified Field Tile

GIAMA2448BGMT
24" x 48"
Matte Rectified Field Tile

DARK GREY





GIAMA2424DGPO
24" x 24"
Polished and Rectified Field Tile



GIAMA1224DGPO
12" x 24" Polished and Rectified Field Tile

GIAMA1224DGMT
12" x 24" Matte Rectified Field Tile

GIAMA2448DGPO
24" x 48"
Polished and Rectified Field Tile

GIAMA2448DGMT
24" x 48"
Matte Rectified Field Tile

LIGHT GREY





GIAMA2424LGPO
24" x 24"
Polished and Rectified Field Tile



GIAMA1224LGPO
12" x 24" Polished and Rectified Field Tile

GIAMA1224LGMT
12" x 24" Matte Rectified Field Tile

GIAMA2448LGPO
24" x 48"
Polished and Rectified Field Tile

GIAMA2448LGMT
24" x 48"
Matte Rectified Field Tile

TAUPE





GIAMA2424TPPO
24" x 24"
Polished and Rectified Field Tile



GIAMA1224TPPO
12" x 24" Polished and Rectified Field Tile

GIAMA1224TPMT
12" x 24" Matte Rectified Field Tile

GIAMA2448TPPO
24" x 48"
Polished and Rectified Field Tile

GIAMA2448TPMT
24" x 48"
Matte Rectified Field Tile

PACKAGING


NOMINAL SIZE	PIECES PER BOX	SQ. FT. PER BOX	LBS. PER BOX	BOXES PER PALLET	SQ. FT. PER PALLET	WEIGHT PER PALLET
12" x 24" Matte Rectified Field Tile	8	15.50	71.68	40	620	2880
12" x 24" Polished and Rectified Field Tile	8	15.50	74.96	40	620	3016
24" x 24" Polished and Rectified Field Tile	4	15.50	74.96	36	558	2700
24" x 48" Matte Rectified Field Tile	2	15.50	84	25	387.50	2100
24" x 48" Polished and Rectified Field Tile	2	15.50	82	25	387.50	2050

TECHNICAL SPECIFICATIONS

DESCRIPTION	RESULT	TEST METHOD (STANDARD)
PEI Rating	4	ASTM C-1027
Water Absorption	0.5%	ASTM C-373
C.O.F. (Dynamic) Matte	0.42	ANSI A137.1
C.O.F. (Dynamic) Polished - NOT COMPLIANT	0.24	ANSI A137.1
Chemical Resistance	Excellent	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Thickness	10 mm	Factory Provided

SHADE VARIATION AND APPLICATIONS

V3



HEAVY VARIATION

	RESIDENTIAL	COMMERCIAL	INDUSTRIAL
Floor	•	•	•
Wall	•	•	•
Countertop	•	•	•