

Featuring GIO Verve, Noce 12x24

verve

GIO
ARCHITECTURAL TILE + STONE

verve

Elegantly earthen modular and mosaic stone-look tiles—authentic details, versatile hues, urbane style

GLAZED PORCELAIN STONEWARE
A NON-TRADITIONAL (MULTI-DIRECTIONAL) VEIN-CUT PRODUCT.

BEIGE



GIVE1224BGE
12″ x 24″
Field Tile



GIVE624BGE
6″ x 24″
Field Tile



GIVE1212BGE
12″ x 12″
Field Tile



GIVEMOSBGE
12″ x 12″
Mosaic



GIVE312BNBGE
3″ x 12″
Bullnose

BIANCO

GIVE1224BI
12″ x 24″
Field Tile

GIVE624BI
6″ x 24″
Field Tile

GIVE1212BI
12″ x 12″
Field Tile



GIVEMOSBI
12″ x 12″
Mosaic

GIVE312BNBI
3″ x 12″
Bullnose

GREY



GIVE1224GR
12″ x 24″
Field Tile



GIVE624GR
6″ x 24″
Field Tile



GIVE1212GR
12″ x 12″
Field Tile



GIVEMOSGR
12″ x 12″
Mosaic



GIVE312BNGR
3″ x 12″
Bullnose

NOCE



GIVE1224NO
12″ x 24″
Field Tile



GIVE624NO
6″ x 24″
Field Tile



GIVE1212NO
12″ x 12″
Field Tile



GIVEMOSNO
12″ x 12″
Mosaic



GIVE312BNNO
3″ x 12″
Bullnose

PACKAGING

NOMINAL SIZE	PIECES PER BOX	SQ. FT. PER BOX	LBS. PER BOX	BOXES PER PALLET	SQ. FT. PER PALLET	WEIGHT PER PALLET
12" x 12" Field Tile	14	13.56	54	44	596.64	2356.20
12" x 24" Field Tile	8	15.54	61	32	497.80	1982.50
6" x 24" Field Tile	13	12.60	55	44	554.40	2436
12" x 12" Mosaic	10	–	37.88	–	–	–
3" x 12" Bullnose	20	–	18.74	–	–	–

TECHNICAL SPECIFICATIONS

DESCRIPTION	RESULT	TEST METHOD (STANDARD)
PEI Rating	4	C1027 Test
Water Absorption	0.05%	C373 Test
C.O.F. (Dynamic)	0.42	ANSI 137.1
Frost Resistance	RESISTANT	ASTM C1026
Chemical Resistance	RESISTANT	ISO 10545.14
Thickness	9 mm	Factory Provided

SHADE VARIATION AND APPLICATIONS

V3



HEAVY VARIATION

	RESIDENTIAL	COMMERCIAL	INDUSTRIAL
Floor	•	•	•
Wall	•	•	•
Countertop	•	•	•

GREEN SQUARED
Certified by UL Environment