

Featuring GIO Rex, Black 24 x 48 Polished and Rectified Bookmatch Field Tile

GIO
ARCHITECTURAL TILE + STONE

rex

Indulge in the unabashed onyx, vein-cut look interpreted in powerful porcelain, offered in 24x48 tiles and four lush neutrals in polished or matte finishes—so classic, sexy, and bold.

INKJET RECTIFIED POLISHED & MATTE FLOOR & WALL
GLAZED PORCELAIN STONEWARE WITH BOOKMATCH OPTION

BLACK



GIARX2448BLKP
24" x 48"
Polished & Rectified Field Tile
GIARX2448BLKM
24" x 48"
Matte & Rectified Field Tile

GREY



GIARX2448GRYP
24" x 48"
Polished & Rectified Field Tile
GIARX2448GRYM
24" x 48"
Matte & Rectified Field Tile

IVORY



GIARX2448IVYP
24" x 48"
Polished & Rectified Field Tile
GIARX2448IVYM
24" x 48"
Matte & Rectified Field Tile

SAND




GIARX2448SNDP
24" x 48"
Polished & Rectified Field Tile
GIARX2448SNDM
24" x 48"
Matte & Rectified Field Tile

PACKAGING

NOMINAL SIZE	PIECES PER BOX	SQ. FT. PER BOX	LBS. PER BOX	BOXES PER PALLET	SQ. FT. PER PALLET	WEIGHT PER PALLET
24" x 48" Polished & Rectified Field Tile	2	15.50	70.74	32	496	2263.68
24" x 48" Matte & Rectified Field Tile	2	15.50	70.54	32	496	2257.28

SHADE VARIATION AND APPLICATIONS

V4



RANDOM VARIATION

	RESIDENTIAL	COMMERCIAL	INDUSTRIAL
Floor	•	•	•
Wall	•	•	•
Countertop	•	•	•

TECHNICAL SPECIFICATIONS

Description	Result	Test Method (Standard)
Chemical Resistance	RESISTANT	C650 Test
Water Absorption	0.5%	ISO 10545-3
PEI	4	C1027 Test
C.O.F. (Dynamic) Matte	0.42	ANSI 137.1
C.O.F. (Dynamic) Polished	Not Compliant	ANSI 137.1
Frost Resistance	RESISTANT	ASTM C1026
Thickness	10 mm	Factory Provided